




PT MARSAT WINDU ANDIKA

Jl. Cinere Raya Blok K/6C, Cinere - Depok 16514, Indonesia
 Tel. : +(62) 21 754 3794 Fax : +(62) 21 753 2742
 http://www.mwa.co.id; email : mw@mwa.co.id

Product Type: DVB-T2 FTA		Remarks
Model Number	MXA-6608	Solution:MSD7T01+RT836
		without Digital Dolby Plus
		without LED display and key
		IR Senser without LED Display: for Option
		IR Senser with LED Display: for Option
Key Features		
<p>Fully supports DVB-T2/T, HD MPEG 2, MPEG4,HD H.264, ,1080i,1080p HDMI for multimedia play, standard and high definition output for DVB-T2 PVR function via USB 2.0 Learning Remote Control which can control the TV Set and STB</p>		
Picture	Input and output	
	USB: USB2.0	
	RF in	
	HDMI output	
	L/R/CVBS	
Main Features	Tuner	
Auto and manually scan all available TV and radio channels	RT836	
Aspect ratio 16:9 and 4:3	RF input frequency: VHF: 174MHz - 230MHz	
OTA upgrade software supported	UHF: 474MHz - 866MHz	
HDMI, L/R/CVBS		
Timer function		
Built-in clock synchronization	Powerful Multimedia Features	
Time Shift function	Photo: JPEG,BMP,PNG	
Fast and slow playback of recordings	Audio: WMA、MP3、AAC (.wma、.mp3、.m4a)	
RF in	Video: MPEG1、MPEG2、MPEG4、H264、	
Parental lock by PIN code	Motion JPEG (.avi.mpg、.dat、.vob、.div、.mov、.mkv、	
DVB Subtitling-ETSI 300473 Compliant and VBI/OSD teletext	.mjpeg、.ts、.trp)	
	NTFS、FAT32、FAT16	
Demultiplexer	Decording	
Standard ISO/IEC 13818-1; ARIB STB-B10	Mpeg transport stream and A/V decoding	
Input max. bit stream rate: 120Mbps (serial)/15MBps (parallel)	Video standard: MPEG-4 AVC/H.264 HP@L4	
	SCART video model CVBS/RGB (for Europe)	
	Aspect ratio: 4:3, 16:9	
	Video resolution: 576i, 576p, 720p,1080i and 1080p	
Demodulation:	Audio standard: ISO/IEC 14.496-3,, AAC, AAC+	
Terrisal Receiver Standard: DVB-T2/T (EN 302755/EN 300744)	Audio mode: mono, dual-channel, stereo	
QPSK, 16QAM, 64QAM, 256QAM		
FEC: 1/2, 2/3, 3/4, 4/5,5/6,		
Guard Interval: 1/4,1/8,1/16,1/32,1/128	Accesaries	
FFT Mode: 2K, 8K,32K	Adapter, Remote Control, Battery, AV Cable, User Manual.	
	IR Senser for option	